# SONY



3LCD Laser Projector



# Why Sony?

Sony is a major professional in the world of imaging technology, across both consumer and professional applications.

Sony's comprehensive imaging technologies extend across a wide range: lenses, image sensors, image processors, IP transmission, display devices and light sources. Products are developed by engineers with deep and broad experience in imaging technologies.

As a leading global manufacturer for professional users, Sony offers superlative moviemaking and broadcasting, as well as medical equipment and business and educational products.



## Image quality




Sony's BrightEra<sup>™</sup> 3LCD panel works with Sony's original Z-Phosphor<sup>™</sup> light source to deliver unmatched clarity, color reproduction and smooth gradation.

Sony's 'Reality Creation' engine delivers ultra-high accuracy by combining database-driven, superresolution processing with image pattern classification. Automatic control of both super-resolution processing and noise reduction ensures stunning image quality, smooth gradations and low noise.



### Intelligent setting



Optimum setting, maximizing performance

Intelligent Settings offer four presets, optimising brightness, cooling system and other projector settings to suit all usage environments.

In addition, VPL-FHZ131L, VPL-FHZ101L, VPL-FHZ91L, VPL-PHZ60, and VPL-PHZ50 are equipped with an Advanced Intelligent Setting function, which automatically control the temperature of the installation environment, frequency of usage, and several other parameters so that they can be used at suitable settings for long-term stable operation.

# Simple and discreet

The projector's minimalist design looks great in any space, blending seamlessly into the background of conference rooms, museums, and other sophisticated locations.

An experienced team of designers have created a functional, aesthetically pleasing product that is durable, easy to set up, and easy to use.



### 3LCD laser projector lineup, by venue

Venue Brightness		Large					
		Halls, Auditoriums	Museums, Galleries	Bright classrooms, Mee			
		13,000 lm	10,000 lm	9,000 lm			
Model name		VPL-FHZ131L	VPL-FHZ101L	VPL-FHZ91L			
Lens shift	Vertical	±107%					
· · ·	(Maximum) Horizontal		±57%				
Lens		Intercha					
	Throw ratio		Depends on lens				
	Resolution			40" + 600"			
Scree	n size	1070.111	40" to 600" 1076 W 840 W				
Power consumption (Maximum)	AC 100 V to 120 V	1076 W					
	AC 220 V to 240 V	1033 W	81	4 W			
	Power requirements			(			
Dimensions (without protrusions) & weight		Approx. 544 x 205 x 564 mm (27 kg)		5 x 564 mm (26 kg)			
Input / output			PC DVI-D HDMI HDBaseT 3G-SDI OULPUL PC/Component 3G-SDI				
Control signal input / output		RS-232C LAN USB A					
Reality creation				•			
Intelligent setting		Version 2	Version 2	Version 2			
Automatic filter cleaning				•			
Edge b	Edge blending			•			
Warping				•			

\*1: support as an option, required BKM-PJ20

\*2: VPL-PHZ60, VPL-PHZ50 and VPL-CWZ10 do not support correcting deflection

### Optional lenses

#### For VPL-FHZ131L/FHZ101L/FHZ91L

Model name	VPLL-Z4107	VPLL-4008	VPLL-Z4111	VPLL-Z4015	VPLL-Z4019	VPLL-Z4025	VPLL-Z4045
Throw ratio	0.75:1 to 0.94:1	1.00:1	1.30:1 to 1.96:1	1.85:1 to 2.44:1	2.41:1 to 3.07:1	3.02:1 to 5.58:1	5.56:1 to 7.5:1
Zoom	Powered	-	Powered	Powered	Powered	Powered	Powered
Focus	Powered	Manual	Powered	Powered	Powered	Powered	Powered
Screen size	60" to 600"	40" to 600"	60" to 600"	40" to 600"	40" to 600"	40" to 600"	60" to 600"
Lens shift (V, H)	±50%, ±24%	±32%, ±15%	±99%, ±51%	±98%, ±51%	±107%, ±57%	±107%, ±57%	±107%, ±57%
Weight	3.3 kg	2.6 kg	4.0 kg	3.0 kg	3.0 kg	2.8 kg	3.0 kg

#### Small



0,500 III	5,500 mm	0,000 min 5,000 min		5,000 III		
VPL-FHZ75	VPL-FHZ70	VPL-PHZ60	VPL-PHZ50	VPL-CWZ10		
-5%,	+70%	-35% to	- N/A (Lens Offset Vertical +37%)			
±3	2%	±1				
ngeable			Fixed			
1.39:1 to 2.23:1 (When u	using the included lens)	1.23:1 t	1.29:1 to 2.07:1			
WUXGA (1920 x 1200)			WXGA (1280 x 800)			
		40" to 300"				
537 W 483 W		44(	342 W			
518 W	468 W	418	3 W	326 W		
AC 100 V	′ to 240 V					
Approx. 460 x 169 x 515 mm (16 kg)		Approx. 422 x 100 x 333 mm (7 kg) Approx. 422 x 100 x 333 mm (6.6 kg)		Approx. 371 x 100 x 319.3 mm (5.7 kg)		
Input 😳 📟 🛄 🕤 🇿 🗋 Output 📟 OU-D Audio		Input 📟 🔵 O PC HDMI Audio HI	DBaseT Video Output O	Input PC HDMI Audio Video Output O Audio		
RS-232C LAN IR (Control S) input		RS-232C LAN USE	RS-232C LAN USB A			
	•			-		
Version 1	Version 1	Versi	Version 1			
	•		-			
		-	-			
			*2	•*2		

💿 BNC 📟 D-sub 15 pin 🔘 RCA 📖 DVI-D 🚍 HDMI 👖 RJ-45 📟 D-sub 9 pin 💿 Stereo mini jack 🔚 USB A 🔚 USB for power supply

#### For VPL-FHZ75/FHZ70

Model name	VPLL-3003	VPLL-3007	VPLL-Z3009	VPLL-Z3010	VPLL-Z3024	VPLL-Z3032
Throw ratio	0.33:1	0.65:1	0.85:1 to 1.0:1	1.0:1 to 1.39:1	2.34:1 to 3.19:1	3.18:1 to 4.84:1
Zoom	-	-	Manual	Powered	Powered	Powered
Focus	Powered	Manual	Manual	Powered	Powered	Powered
Screen size	80" to 300"	60" to 300"	60" to 300"	60" to 300"	40" to 600"	40" to 600"
Lens shift (V, H)	±5%, ±5%	+10%/-5%, +/-4%	+50%/-5%, ±24%	+60%/-5%, +/-29%	+60%/-5%, +/-32%	+60%/-5%, +/-32%
Weight	2.9 kg	1.7 kg	1.7 kg	2.0 kg	1.2 kg	1.2 kg



 VPL-FHZ131L
 13,000 Im, WUXGA

 VPL-FHZ101L
 10,000 Im, WUXGA

 VPL-FHZ91L
 9,000 Im, WUXGA

### VPL-PHZ60 6,000 Im WUXGA VPL-PHZ50 5,000 Im WUXGA

- Installation flexibility
  - Very wide range of lens shift adjustment and a wide choice of interchangeable lenses including VPLL-Z4107 short throw lens
- Networked control and monitoring
  - Ideal for integration in AV environments with leading control, monitoring and management systems such as Crestron Connected<sup>®</sup> and Extron<sup>®</sup> XTP<sup>™</sup> Systems.\*

\* Extron and XTP Systems are trademarks of RGB Systems Inc.

- Bright View
  - Bright View delivers easy-to-see images, even in bright environments
- Installation flexibility
  - Enjoy easy installation and greater flexibility with lens shift to position the projector in higher spaces
  - Supports for 4K 30P input signals and wide range of major control interfaces
- Networked control and monitoring
  - Ideal for integration in AV environments with leading control, monitoring and management systems such as Crestron Connected<sup>®</sup> and Extron<sup>®</sup> XTP<sup>™</sup> Systems.\*

\* Extron and XTP Systems are trademarks of RGB Systems Inc.



VPL-CWZ10 5,000Im, WXGA

- Affordable 3LCD laser projector
  - Quick power on/off
  - Consistent brightness
  - Reduced maintenance
- Lightweight, compact blend-in design

## SONY

Distributed by

#### https://pro.sony/projectors

©2020 Sony Home Entertainment & Sound Products Inc.

- Reproduction in whole or in part without written permission is prohibited.
- Features and specifications are subject to change without notice.

The values for mass and dimension are approximate.

"SONY" is a registered trademark of Sony Corporation.

"Z-Phosphor" and "BrightEra" are trademarks of Sony Corporation.

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or

registered trademarks of HDMI Licensing LLC in the United States and other countries.

 $\mathsf{HDBaseT^{IM}}$  and the  $\mathsf{HDBaseT}$  Alliance logo are the trademarks of the  $\mathsf{HDBaseT}$  Alliance.

Crestron Connected is trademarks of Crestron Electronics, Inc.

All other trademarks are the property of their respective owners.

Please visit Sony's professional website or contact your Sony representative for specific models available in your region.

HESMK0002V1YIT20NOV